



Department of consumer and corporate affairs / Ministère de la consommation et des corporations
STANDARDS BRANCH - DIRECTION DES NORMES

NOTICE OF APPROVAL

S.WA-629

Revision 2

OTTAWA January 20, 1970.

Approved: CLASSIC - REBUILT GASOLINE DISPENSERS MODELS 140B-1, 540W-DUAL 02, 640GB, 740GB-DUAL 02, 840W-DUAL 02, 940W-DUAL 01.

manufactured by: Classic Pump Manufacturers Ltd., Ottawa, Ontario.

Apparatus Listed: Computing type gasoline dispensers, which use overhauled working components from older approved dispensers; model numbers of the new dispensers are as follows:

<u>Model No.</u>	<u>Description</u>
140B-1	Dispenser with single suction pump and single hose; uses overhauled working components from Bowser model 2500.
240GB-Dual 01	Dispenser with single suction pump and two hoses; uses overhauled working components from Gilbarco model 1006.
240T-Dual 01	Dispenser with single suction pump and two hoses; uses overhauled working components from Tokheim series 452.
540BT-Dual 02	Dispenser with two suction pumps and two hoses; uses overhauled working components from Bennett model 956.
540T-Dual 02	Dispenser with two suction pumps and two hoses; uses overhauled working components from Tokheim model 452.
540W-Dual 02	Dispenser with double suction pumps and two hoses; uses overhauled working components from Wayne model 500-Duo 2, including the original Gilbert and Barker 4-piston meter used in that particular Wayne dispenser.
640GB	Dispenser for remote pump, with one hose; uses overhauled working components from Gilbert and Barker model 1006.

- 740GB-Dual 02 Dispenser for remote pumps, with two hoses for two products; uses overhauled working components from Gilbert and Barker model 1006.
- 840W-Dual 02 Dispenser with two suction pumps and two hoses for two products; uses overhauled working components from Wayne model 500 single dispensers, including the Wayne 4-piston meter.
- 940W-Dual 01 Dispenser for remote pump with two hoses for single product; uses overhauled working components from Wayne model 500 for remote pump.

Rating of Apparatus: Maximum capacity 12 gpm.


Application: Retail gasoline trade.


Description: These dispensers use the same housing as the dispensers listed in S.WA-609. All the working components from the original dispensers are used, except the sight glass, and they are installed in the same arrangement as in the original dispenser. The components are thoroughly overhauled to perform substantially as well as new ones. Either manual or semi-automatic reset may be used.

Tests: The standard tests for a gasoline dispenser shall apply.

References: SW-85-S4
SL-102-61 I

Note: Approval is granted under the Weights and Measures Act, Chapter 292, and Regulations thereunder (P.C. 6894) for use in Canada under the general conditions of P.C. 6894, and under any special conditions listed above.


(for) Chief,
Weights and Measures Division,
Standards Branch.


R. W. MacLean,
Director,
Standards Branch.