



Department of consumer and corporate affairs / Ministère de la consommation et des corporations



STANDARDS BRANCH - DIRECTION DES NORMES

NOTICE OF APPROVAL

S.WA-684

OTTAWA January 23, 1970.

Approved: TOKHEIM - GASOLINE DISPENSERS WITH TICKET PRINTERS AND KEY CONTROLLED TOTALIZERS
manufactured by: Tokheim of Canada Limited, Toronto

Apparatus Listed: Non-computing type gasoline dispensers equipped with ticket printers and/or key-controlled subsidiary totalizers, model numbers as follows:

<u>Model No.</u>	<u>Description</u>
485-V-KC-4, -8, -16	Model 485 dispenser with 4, 8 or 16 key-controlled subsidiary totalizers, as indicated by the suffix.
485-V-TP-KC-4, -8, -16	Model 485 dispenser with ticket printer and 4, 8 or 16 key-controlled subsidiary totalizers, as indicated by the suffix.
486-HS-V-KC-4, -8, -16	Model 486-HS dispenser with key-controlled subsidiary totalizers.
486-HS-V-TP-4, -8, -16	Model 486-HS dispenser with ticket printer and key-controlled subsidiary totalizers.
486-D-V-KC-4, -8, -16	Model 486-D dispenser with key-controlled subsidiary totalizers.
486-D-V-TP-KC-4, -8, -16	Model 486-D dispenser with ticket printer and key-controlled subsidiary totalizers.

The meaning of the suffixes used with the above model numbers is as follows:

- | | |
|-------------------|---------------------|
| V - sight glass | RC - remote pump |
| HS - high speed | PR - power reset |
| D - high capacity | TP - ticket printer |
| PR - power reset | KC - key control |

Rating of Apparatus: Maximum capacity of 485 is 12 gpm.
Maximum capacity of 485HS and 486D is 18.5 gpm.


Application: Retail gasoline trade.


Description: These dispensers are identical to those listed on S.WA-612 except that ticket printers and key-controlled subsidiary totalizers for individual customers have been added. The ticket printer is interlocked so that it is impossible to deliver other than the quantity stamped on the ticket; product may be delivered without a ticket being inserted, but the delivery will be recorded on the individual totalizer. The shutters on the totalizers must be sealed in a position to expose the totalizers, otherwise the totalizers must be labelled "not legal for trade".

Testing: The standard tests for a gasoline dispenser shall apply. In addition, the effectiveness of the printer interlocks shall be checked.

References: SW-85-T4
SL-102-624
Letter of approval of July 20, 1967

Note: Approval is granted under the Weights and Measures Act, Chapter 292, and Regulations thereunder (P.C. 6894) for use in Canada under the general conditions of P.C. 6894, and under any special conditions listed above.


(for) Chief,
Weights & Measures Division,
Standards Branch.


R. W. MacLean,
Director,
Standards Branch.